INTEK[™] 19.0 GROSS HP[†]

540 CC

Bore 3.70 in. (94.00 mm) Stroke 3.06 in. (77.80 mm) Oil Capacity 48 fl. oz. (1.40 L)



FEATURES:


Full pressure lubrication with premium oil and fuel filters provide longer maintenance intervals and greater longevity


Advanced Debris Management System with our largest dual seal, cartridge-style air filter that provides maximum protection and extends engine life

Chrome plated exhaust valves reduce valve wear, providing longer life

Super-finished crank pin bearing reduces friction and heat to minimize wear under heavy load, for long life Mechanical Governor

Buyer protection package provides two-year limited consumer engine warranty**





| мтт | Crankshaft# | P.T.O. Diameter | Drilled & Tapped | Keyway | Length | Starter Position | Controls | Fuel Pump, Integral | Oil Pump with Filter | Choke-A-Matic | ReadyStart® | Ground Wire Terminal | Remote Stop | Fuel Tank (Quarts) | Top Governor Speed | Notes |
|---------|-------------|-----------------|------------------|----------|--------|------------------|----------|---------------------|----------------------|---------------|-------------|----------------------|-------------|--------------------|--------------------|-------|
| 33R877 | | | | | | | | | | | | | | | | |
| 0003-G1 | 591763 | 1 in. | 7/16-20 | 1/4-Str. | 3-5/32 | | R | Х | Х | Х | | Х | | | 3600 | 5.14 |

[†]All power levels are stated gross horsepower at 3600 RPM per SAE J1940 as rated by Briggs & Stratton.

Engines in bold type have promotional pricing

⁽⁵⁾ Engine equipped with 12 volt Gear Drive Starter and 9 Amp DC Alternator

⁽¹⁴⁾ Supress Afterfire Solenoid